

MOLD OIL N02

Product Description

MOLD OIL N02 is full-oil based mold release for concrete with no ingredient of solvent. Specialized formulation lead to smooth surface, excellent ability to release for general shape. Suitable for variety precast applications such as wall, floor and hollow core slab. It is designed to enhance easily cleaning, prevent adhesive between concrete surface and mold surface in order to provide aesthetical appearance.

Benefits

- Ease to release from molds
- Provide dominant smooth and no stain on surface
- Excellent film strength on mold surface
- None volatile and odorless
- Excellent rust preventive toward molds
- High flash point with inflammable

Applications

- Conventional spray equipment, brush or roller directly on mold surface with thin film
- Surface should be cleaned, free from dirt, grease or old concrete remains

The Moving Innovation=



MOLD OIL N02

Typical Characteristics

Tests	Methods	Units	Results
Appearance	Visual Inspection		Colorless
Density at 30 °C	ASTM D4052-11	g/ml	0.8233
Kinematic Viscosity at 40 °C	ASTM D445-11	mm²/s	8.119
Flash Point (COC)	ASTM D92	°C	154

Health and Safety

This product shows no significant health or safety hazard when used under the recommended applications and suitable handling.

Avoid the direct contact. Wash immediately after contact. Health and safety information is available on the Safety Data Sheet (SDS) which can be obtained from http://pttlubricants.pttor.com





Note: Data and information contained in this publication are based on standard test under laboratory conditions and/or performance test. To consider the use of PTT Lubricants' products in particular application, customer is responsible for determining whether product and information are appropriate for customer conditions or should consult with PTT Lubricants' technical service division. The procedure of using any lubricant may differ or change depended on different machines and their manuals. Therefore, we recommend to read, understand and review the latest SDS in order to ensure the use of product is accomplished safety.

The Moving Innovation