



PTT CLEARA SYNTHETIC

Fully Synthetic High-Temperature Oil

Descriptions

- *PTT CLEARA SYNTHETIC 220*: is fully synthetic high-temperature oil for glass manufacturer which is suitable for used in Individual Section (IS) machine. High quality synthetic base oil is used to provide long service life and is blended with advanced additive technologies which gives excellent thermal stability and wear protection. *PTT CLEARA SYNTHETIC* provides excellent resistance to deposit and sludge formation, high wear reduction rates as well as good corrosion protection.

Special Properties

- Superior lubricant performance especially high operating temperature leading to minimize wear and extend machine life
- Excellent low volatility gives low oil consumption
- Outstanding oxidation and thermal stability resist to deposit and sludge formation from thermal degradation
- Stable, non-corrosive, high flash point and high viscosity index liquid.

Application

- All Individual Section machine
- All chain lubrication in all range of temperature

Reference Standards

Typical Values

	220
- Viscosity @ 40 °C, cSt	221.3
- Viscosity index	150.8
- Specific gravity @ 30 °C	0.9083
- Flash point COC, °C	304
- Pourpoint, °C	-33
- Copper Strip Corrosion	1b
- Rust Protection	Pass
- Foam Seq I, ml/ml	nil/0
Seq II, ml/ml	nil/0
Seq III, ml/ml	nil/0

For more information, please contact Lubricants Technical Services Division, PTT Public Company Limited : Tel. (662) 239-7911, (662) 239-7908
Fax. (662) 239-7858