

PERFORMA RD-2

SAE 10W-60

Product Description

PERFORMA RD-2 is ultimate fully synthetic competition-proven motor oil advanced technology to deliver extreme performance by maximizing and maintaining engine power for racing purpose. It is designed with HFS (High Film Strength) Technology offering extra film strength to enhance outstanding thermal resistance and engine wear protection even in high rpm and enable acceleration response by special friction modifier.

Benefits

- Extra strong oil film for engine protection even in most extreme race.
- Enhanced with special anti-wear additive for supreme engine wear protection and enhances accelerating performance with exceptional acceleration booster.
- Fortify with supreme lubricity characteristic for all racing temperature range and circuit conditions.
- Offers high thermal and oxidation stability, leading to oil sludge and oil screen clogging prevention.
- Field proven with racing cars in various circuit types.

Applications

- Designed for modified racing engine in all motorsport activities such as circuit racing, drag racing and drift competition.
- Recommended for high performance modified engine.

The Moving Innovation 

PERFORMA RD-2

SAE 10W-60

Typical Characteristics

Tests	Methods	Units	Results 10W-60
Density at 15 °C	ASTM D 4052	g/cm ³	0.854
Kinematic Viscosity at 40 °C	ASTM D 445	mm ² /s	165.7
Kinematic Viscosity at 100 °C	ASTM D 445	mm ² /s	23.9
Viscosity Index	ASTM D 2270		175
Cold-cranking Simulator at -30°C	ASTM D 5293	mPa.s	5,100
Flash Point (COC)	ASTM D 92	°C	242
Pour Point	ASTM D 5950	°C	-45

Performance Standards

- API SH

Health and Safety

This product shows no significant health or safety hazard when used under the recommended applications and suitable handling.

Avoid the direct contact. Wash immediately after contact. Health and safety information is available on the Safety Data Sheet (SDS) which can be obtained from <http://pttlubricants.pttor.com>



The product can cause some skin irritation and has flash point higher than 93.4°C

Note: Data and information contained in this publication are based on standard test under laboratory conditions and/or performance test. To consider the use of PTT Lubricants' products in particular application, customer is responsible for determining whether product and information are appropriate for customer conditions or should consult with PTT Lubricants' technical service division. The procedure of using any lubricant may differ or change depended on different machines and their manuals. Therefore, we recommend to read, understand and review the latest SDS in order to ensure the use of product is accomplished safety.

The Moving Innovation 