

# **HI-SPEED 2T**

#### **Product Description**

HI-SPEED 2T is a high quality 2-stroke motorcycle oil developed to protect piston scratch and ring sticking problems for all models of bikes. It prevents spark plug fouling and reduces exhaust smoke.

### **Benefits**

- Formulates with PIB (Polyisobutylene) synthetic base stock for extremely clean combustion and reduces white smoke and deposits.
- Increases lubricity efficiency and provides good engine cleanliness.
- Prevents piston and ring sticking and spark plug fouling.
- Protects exhaust port blocking.

### Applications

- Recommended for all models air and water-cooled of 2-stroke motorcycles and multipurpose 2-stroke engine.
- Suitable for both oil injection and premix system.
- Fuel/Oil ratio required following by the manufacturers' recommendations.

## The Moving Innovation=



# **HI-SPEED 2T**

_		<b>A</b> 1		
ΤV	nical	Chara	cteris	tics
	p our	<b>Under a</b>		

Tests	Methods	Units	Results
Density at 15 °C	ASTM D 4052	g/cm <sup>3</sup>	0.869
Kinematic Viscosity at 40 °C	ASTM D 445	mm²/s	70.2
Kinematic Viscosity at 100 °C	ASTM D 445	mm²/s	9.9
Viscosity Index	ASTM D 2270		123
Flash Point (COC)	ASTM D 92	°C	92
Pour Point	ASTM D 5950	°C	-15
Sulphated Ash	ASTM D 874	% wt	0.1

### **Performance Standards**

- JASO FC
- API TC
- TIS 1040-1998

### Health and Safety

This product shows no significant health or safety hazard when used under the recommended applications and suitable handling.

Avoid the direct contact. Wash immediately after contact. Health and safety information is available on the Safety Data Sheet (SDS) which can be obtained from http://pttlubricants.pttor.com

PTT LUBE Professional Lubricant

The product can cause some skin irritation.

Note: Data and information contained in this publication are based on standard test under laboratory conditions and/or performance test. To consider the use of PTTOR Lubricants' products in particular application, customer is responsible for determining whether product and information are appropriate for customer conditions or should consult with PTTOR Lubricants' technical service division. The procedure of using any lubricant may differ or change depended on different machines and their manuals. Therefore, we recommend to read, understand and review the latest SDS in order to ensure the use of product is accomplished safety.

The Moving Innovation=