

MAX SPEED 2T

Product Description

MAX SPEED 2T is 2-stroke motorcycle oil developed to provide high wear protection. It reduces exhaust smoke.

Benefits

- Provides good engine cleanliness.
- Prevents piston and ring sticking.
- Increases lubricity efficiency.

Applications

- Recommended for 2-stroke motorcycles and multipurpose 2-stroke engine.
- Suitable for both oil injection and premix system.
- Fuel/Oil ratio required following by the manufacturers' recommendations.

The Moving Innovation 

MAX SPEED 2T

Typical Characteristics

Tests	Methods	Units	Results
Density at 15 °C	ASTM D 4052	g/cm ³	0.863
Kinematic Viscosity at 40 °C	ASTM D 445	mm ² /s	56.2
Kinematic Viscosity at 100 °C	ASTM D 445	mm ² /s	8.9
Viscosity Index	ASTM D 2270		115
Flash Point (COC)	ASTM D 92	°C	113
Pour Point	ASTM D 5950	°C	-15
Sulphated Ash	ASTM D 874	% wt	0.1

Performance Standards

- TIS 1040-1998

Health and Safety

This product shows no significant health or safety hazard when used under the recommended applications and suitable handling.

Avoid the direct contact. Wash immediately after contact. Health and safety information is available on the Safety Data Sheet (SDS) which can be obtained from <http://pttlubricants.pttor.com>



The product can cause some skin irritation.

Note: Data and information contained in this publication are based on standard test under laboratory conditions and/or performance test. To consider the use of PTTOR Lubricants' products in particular application, customer is responsible for determining whether product and information are appropriate for customer conditions or should consult with PTTOR Lubricants' technical service division. The procedure of using any lubricant may differ or change depended on different machines and their manuals. Therefore, we recommend to read, understand and review the latest SDS in order to ensure the use of product is accomplished safety.

The Moving Innovation 