

POWERTRAC 7884

SAE 30

Product Description

POWERTRAC 7884 is high performance Tractor Hydraulic Fluid (THF). It's produced from high quality base oil and high performance multi-functional additive for providing hydraulic and gear protection and also enable proper friction for wet brake and reduce chatter noise along with prolong oil drain interval. Suitable for hydraulic system, transmission differential and wet brake of modern agricultural tractor.

Benefits

- Prevents wear and endures damage from heat and oxygen.
- Enables all-the-time-wet brake and clutch to work efficiently without slipping and loud noise occurring.
- Durable to water and has corrosion, rust and bubbles preventive properties.
- Free from engine oil filter plugging problem in hydraulic system.

Applications

- Designed for hydraulic systems, transmissions differentials and wet brakes of conventional agricultural tractor.
- Suitable for transmissions and hydraulic systems required viscosity grade SAE 30.

The Moving Innovation 

POWERTRAC 7884

SAE 30

Typical Characteristics

Tests	Methods	Units	Results
			30
Density at 15 °C	ASTM D 4052	g/cm ³	0.891
Kinematic Viscosity at 40 °C	ASTM D 445	mm ² /s	102.9
Kinematic Viscosity at 100 °C	ASTM D 445	mm ² /s	11.43
Viscosity Index	ASTM D 2270		97
Flash Point	ASTM D 92	°C	250
Pour Point	ASTM D 5950	°C	-9

Performance Standards

- Meet the requirements of FORD, MASSEY FERGUSON AND JOHN DEERE.

Health and Safety

This product shows no significant health or safety hazard when used under the recommended applications and suitable handling.

Avoid the direct contact. Wash immediately after contact. Health and safety information is available on the Safety Data Sheet (SDS) which can be obtained from <http://pttlubricants.pttor.com>

PTT LUBE SOLUTIONS Professional Lubricant Service Partner



The product can cause some skin irritation and has flash point higher than 93.4°C

Note: Data and information contained in this publication are based on standard test under laboratory conditions and/or performance test. To consider the use of PTTOR Lubricants' products in particular application, customer is responsible for determining whether product and information are appropriate for customer conditions or should consult with PTTOR Lubricants' technical service division. The procedure of using any lubricant may differ or change depended on different machines and their manuals. Therefore, we recommend to read, understand and review the latest SDS in order to ensure the use of product is accomplished safety.

The Moving Innovation